

CARBON DIOXIDE FIRE EXTINGUISHER

RESGUARDO[®]



Carbon-dioxide gas media is non-conductive, non-contaminating, non-residual and is suitable for clean environments such as IT, ITES, Pharma, Food processing etc.



MANGANESE STEEL BODY		
Capacity	2 Kg	4.5 Kg
Fire Rating	21B	55B
Diameter (MM)	108±1	139±1
Total Height (MM)	565±2	710
Empty Weight (KG) Approx.	6.5	12
Full Weight (KG) Approx.	8.5 kg	16.5 kg
Avg. Effective Discharge time	08 SEC.	12 SEC.
Volume (L)	3	6.8
Operating Temperature	-30°C TO +60°C	-30°C TO +60°C
Service Pressure	60 bar	60 bar
Max Service Pressure	75 bar	75 bar
Test Pressure	250 bar	250 bar

CARBON DIOXIDE FIRE EXTINGUISHER

Carbon-dioxide gas media is non-conductive, non-contaminating, non-residual and is suitable for clean environments such as IT, ITES, Pharma, Food processing etc. As body is made out of Aluminium, weight of extinguisher is very less, easy to handle during operation.



ALUMINIUM BODY		
Capacity	2 Kg	4.5 Kg
Fire Rating	21B	55B
Diameter (MM)	111±1	140±1
Total Height (MM)	545	705±2
Empty Weight (KG) Approx.	3.2	5.8
Full Weight (KG) Approx.	5.2 kg	10.3 kg
Avg. Effective Discharge time	08 SEC.	12 SEC.
Volume (L)	3.1	6.8
Operating Temperature	-30°C TO +60°C	-30°C TO +60°C
Service Pressure	60 bar	60 bar
Max Service Pressure	75 bar	75 bar
Test Pressure	190 bar	190 bar

