CLEAN AGENT FIRE EXTINGUISHER





HFC-236 FA Clean Agent (Low pressure) is an advanced friendly zero ozone depletion gas. This media is exclusively designed for areas with sensitive equipments such as computer rooms, libraries, museums, laboratories, data processing centers, Industrial process control rooms, chemical storage rooms etc.

COMPARATIVE ADVANTAGES

- Environment friendly replacement for Ha Ion 1211
- Clean and Insulative
- Efficient and leaves no residue
- Does not deplete ozone layer in atmosphere
- Safe for people
- Discharged as gas boiling point is 14°C











Product Name	HFC-236FA	
Chemical Formula	1,1,1,3,3,3- Hexa Fluoro Propane	
Molecular Weight	152	
Boiling Point	-1.4°C	
Freezing Point	-103°C	
Maximum Fill Density	1.20gm/ml	
Specific Gravity	1.34gm/ml	
Scheduled Production Phase		
Out as per Montreal Protocol	None	

Capacity	2KG	4KG	6KG
Fire Rating	1A 21B	2A 34B	2A 55B
Diameter (MM) Approx.	107±0.5	140±0.5	160±0.5
Total Height (MM)	380±2	449	492
Empty weight (KG) Approx.	1.2	2	2.3
Full weight (KG) Approx.	3.2	6	8.3
Avg. Effective Discharge Time	10 SEC.	16 SEC.	20 SEC.
Operating temperature	-20°C TO +60°C	-20°C TO +60°C	-20°C TO +60°C
Service Pressure	15 BAR	15 BAR	15 BAR
Maximum Service Pressure	17 BAR	17 BAR	17 BAR
Test Pressure	35 BAR	35 BAR	35 BAR